

	Ready-To-Run												Assembly Kits	
	TRX-4 Sport	TRX-4 Sport w/Traxx	TRX-4 Land Rover Defender	TRX-4 1979 Bronco	TRX-4 1979 Blazer	TRX-4 2021 Bronco	TRX-4 K10 Blazer High Trail Edition	TRX-4 F-150 High Trail Edition	TRX-6 Mercedes-Benz G 63 AMG 6X6	TRX-6 Ultimate RC Hauler	TRX-4M Defender	TRX-4M Bronco	TRX-4 Sport Kit	TRX-4 Chassis Kit
Model	82024-4	82034-4	82056-4	82046-4	82076-4	92076-4	92056-4	92046-4	88096-4	88086-84	97054-1	97074-1	82010-4	82016-4
Portal Axles	•	•	•	•	•	•	•	•	•	•			•	•
T-Lock Differentials	Optional*	Optional*	•	•	•	•	•	•	•	•	Locked Axles	Locked Axles	Optional*	•
High / Low Transmission	Optional*	Optional*	•	•	•	•	•	•	•	•	Optional Ratios**	Optional Ratios**	Optional*	•
Pinion / Spur Gear	17 / 39 (2.29:1)	11 / 45 (4.09:1)	11 / 45 (4.09:1)	11 / 45 (4.09:1)	11 / 45 (4.09:1)	11 / 45 (4.09:1)	10 / 45 (4.50:1)	10 / 45 (4.50:1)	11 / 45 (4.09:1)	9 / 45 (5.00:1)	16.6:1 (Standard)	16.6:1 (Standard)	17 / 39 (2.29:1)	11 / 45 (4.09:1)
1st Gear Ratio	2:1	2:1	2:1	2:1	2:1	2:1	2:1	2:1	2:1	2:1	40.3:1 (Crawl)**	40.3:1 (Crawl)**	2:1	2:1
2nd Gear Ratio			1.25:1	1.25:1	1.25:1	1.25:1	1.25:1	1.25:1	1.25:1	1.25:1	9.7:1 (Speed)**	9.7:1 (Speed)**		1.25:1
Wheels	Black 5-Spoke	TRAXX w/ Optional Wheels Included	Black 12-Spoke	10-Hole Chrome Replica w/ Caps	8-Hole Chrome Replica w/ Caps	Gloss Black Wildtrak Replica	8-Hole Chrome Replica w/ Caps	5-Slot Chrome Replica w/ Caps	Gray Replica w/Caps	Black Chrome Big Rig w/ Caps	Black 6-Spoke	Black 6-Spoke	Black 5-Spoke	Black 5-Spoke
Wheel Dimensions	1.9" x 1.02" (49 x 26 mm)	1.9" x 1.02" (49 x 26 mm)††	1.9" x 1.02" (49 x 26 mm)	1.9" x 1.02" (49 x 26 mm)	1.9" x 1.02" (49 x 26 mm)	1.9" x 1.02" (49 x 26 mm)	2.2" x 1.34" (56 x 34 mm)	2.2" x 1.34" (56 x 34 mm)	2.6" x 1.02" (66 x 26 mm)	2.2" x 1.02" (56 x 26 mm)	1.0" x 0.49" (25.4 x 12.5 mm)	1.0" x 0.49" (25.4 x 12.5 mm)	1.9" x 1.02" (49 x 26 mm)	1.9" x 1.02" (49 x 26 mm)
TIRES	1.9" x 4.64" Canyon Trail	1.9" x 4.64" Canyon Trail††	1.9" x 4.64" Canyon Trail	1.9" x 4.64" Canyon Trail	1.9" x 4.64" Canyon Trail	1.9" x 4.64" Canyon Trail	2.2" x 5.3" Canyon Trail	2.2" x 5.3" Canyon Trail	2.6" x 4.64" All-Terrain	2.6" x 4.64" Canyon RT	1.0" x 2.2" Canyon AT	1.0" x 2.2" BFGoodrich	1.9" x 4.64" Canyon Trail	1.9" x 4.64" Canyon Trail
TRAXX	Optional	•	Optional	Optional	Optional	Optional	Optional	Optional	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Optional	Optional
Expedition Rack	Optional	•									Not Compatible	Not Compatible	•	
Body	Painted	Painted	Painted	Painted	Painted	Painted	Painted	Painted	Painted	Painted	Painted	Painted	Clear	Sold Separately
Clipless Body Mounts						•	•	•			•	•		
LED Lighting	Optional	•	Optional	Optional	Optional	Optional	Optional	Optional	•	•	•	•	Optional	Optional
Inner Fenders	Optional	Narrow	Body Mounted	Wide	Wide	Narrow	Wide	Wide	Narrow	Wide (Front)			Optional	Wide
Servo	2075X Metal Gear	2270 Metal Gear	2075X Metal Gear	2075X Metal Gear	2075X Metal Gear	2075X Metal Gear	2075X Metal Gear	2075X Metal Gear	2075X Metal Gear	2075X Metal Gear	2065T	2065T	Sold Separately	2075X Metal Gear
Speed Control	XL-5 HV	XL-5 HV	XL-5 HV	XL-5 HV	XL-5 HV	XL-5 HV	XL-5 HV	XL-5 HV	XL-5 HV	XL-5 HV	ECM 2.5	ECM 2.5	Sold Separately	XL-5 HV
Motor	Titan 550 21T	Titan 550 21T	Titan 550 21T	Titan 550 21T	Titan 550 21T	Titan 550 21T	Titan 550 21T	Titan 550 21T	Titan 550 21T	Titan 550 21T	Titan 180 87T	Titan 180 87T	Sold Separately	Titan 550 21T
Transmitter	TQ 2-Channel	TQ 2-Channel	TQi 4-Channel	TQi 4-Channel	TQi 4-Channel	TQi 4-Channel	TQi 4-Channel	TQi 4-Channel	TQi 4-Channel	TQi 4-Channel	TQ 2-Channel	TQ 2-Channel	Sold Separately	TQi 4-Channel
Receiver	TQ 3-Channel	TQ 3-Channel	TQi 5-Channel	TQi 5-Channel	TQi 5-Channel	TQi 5-Channel	TQi 5-Channel	TQi 5-Channel	TQi 5-Channel	TQi 5-Channel	ECM 2.5	ECM 2.5	Sold Separately	TQi 5-Channel
Length	21.9" (557 mm)	21.9" (557 mm)	23.1" (586 mm)	20.6" (523 mm)	20.6" (523 mm)	23" (584 mm)	22.20" (563 mm)	22.30" (566 mm)	25.6" (651 mm)	37.5" (953 mm)	11" (279 mm)	10.3" (262 mm)	21.9" (557 mm)	20.57" (523 mm)
Track	9.8" (249 mm)	10.5" (266 mm)	9.8" (249 mm)	9.8" (249 mm)	9.8" (249 mm)	9.8" (249 mm)	10.60" (270 mm)	10.60" (270 mm)	9.8" (249 mm)	9.8" (249 mm)	4.9" (124 mm)	4.9" (124 mm)	9.8" (249 mm)	9.8" (249 mm)
Ground Clearance	3.1" (80 mm)	3.5" (90 mm)	3.1" (80 mm)	3.1" (80 mm)	3.1" (80 mm)	3.1" (80 mm)	4" (99 mm)	4" (99 mm)	3.1" (80 mm)	3.1" (80 mm)	1.12" (29 mm)	1.12" (29 mm)	3.1" (80 mm)	3.1" (80 mm)
Weight	5.8 lb (2.63 kg)	8.7 lb (3.9 kg)	7.4 lb (3.37 kg)	6.4 lb (2.91 kg)	6.3 lb (2.84 kg)	6.4 lb (2.91 kg)	7.38 lb (3.35 kg)	7.34 lb (3.33 kg)	8.8 lb (3.99 kg)	10.7 lb (4.83 kg)	1.06 lb (483 g)	1.03 lb (468 g)	5.8 lb (2.63 kg)	6.4 lb (2.91 kg)
Height	9.5" (241 mm)	10.3 in. (261 mm)	11.5" (292 mm)	10.5" (266 mm)	10.1" (255 mm)	9.4" (239 mm)	10.89" (277 mm)	10.82" (275 mm)	10.8" (274 mm)	11.9" (303 mm)	5.3" (135 mm)	4.6" (117 mm)	9.5" (241 mm)	10.47" (266 mm)
Wheelbase	12.3" (312 mm)	12.3 in. (312 mm)	12.8" (324 mm)	12.3" (312 mm)	12.3" (312 mm)	12.8" (324 mm)	13.23" (336 mm)	13.23" (336 mm)	12.8" (324 mm)†	18.6" (471 mm)†	6.1" (155 mm)	6.1" (155 mm)	12.3" (312 mm)	12.3" (312 mm)
Approach Angle	58.8°	76°	56.5°	76°	59°	63.8°	70°	73.5°	60°	60°	52°	54°	58.8°	63.8°
Breakover Angle	45.8°	76°	41.7°	43.2°	47°	49°	52°	49.7°	55°	55°	45°	45°	45.8°	43.2°
Departure Angle	59°	81°	57°	59°	59°	58°	57°	57°	57°	57°	41°	48°	59°	59°
Shock Length	3.5" (90 mm)	3.5" (90 mm)	3.5" (90 mm)	3.5" (90 mm)	3.5" (90 mm)	3.5" (90 mm)	4.33" (110 mm)	4.33" (110 mm)	3.5" (90 mm)	3.5" (90 mm)	2.0" (51 mm)	2.0" (51 mm)	3.5" (90 mm)	3.5" (90 mm)

*Requires 4-channel radio upgrade **Requires optional gear set installation †Wheelbase to intermediate axle ††Included optional tires